



TECHNICAL DATA SHEET

LURF® CLASSIC LAVI GENERAL SPECIFICATIONS

Width	180 mm
Length	1220 mm
Total Thickness	5 mm
Number of Panels per Pack	10 Panels
M ² per Pack	2,196 m ²
Weight per Pack	24,2 kg
Wear Layer	0.5 mm
Tongue and Groove	Uniclic
Usage Class	Class 32

FACTORY WARRANTY


CE	EN 14041: 2004 / AC: 2006	
Warranty	Residential Use	10-Year
	Commercial Use	2-Year
	Uniclic (Residential Use)	10-Year

TECHNICAL SPECIFICATIONS

	STANDARD	LAVI VALUES
Wear Resistance	EN 660-1/2	Group T
Impact Resistance	NALFA LF 01-2011 Section 3.6	No Cracking or Fracture
Dimensional Variance	ISO 24337	Pass
Flexibility	EN 435 Method A	Pass
Castor Chairs Suitability	EN 425	> 25000 Cycles
Chemical Resistance	EN 423	Pass
Residual Indentation	ISO 24343-1: 2007	0.02 mm
Sound Reduction	EN ISO 717-2	2 dB
Curling	EN ISO 23999	-0.15 mm
Locking Strength	ISO 24334	Pass
Electrical Resistance	EN 1815: 2016 Method A	Voltage: 0.2 kV
Dimensional Stability	EN ISO 23999	X Direction: 0.06%
		Y Direction: -0.05%
Reaction to Fire	EN 14041 / ASTM 648	Bfl-S1, Class 1
Colour Fastness to Artificial Light	ISO 105 B02: 2014	>= Grade 6
Slip Resistance	EN 13893	Class DS
Sound Testing	ASTM E90	STC: 68
	ASTM E492	IIC: 66
	ASTM E2179	Delta: 22
Thermal Resistance	EN 12664	0.12 K/W

ENVIRONMENT & CERTIFICATES

VOC Emission		A+ (French VOC Regulation)
Indoor Air Comfort		Gold
GreenGuard		Gold
Formaldehyde Emission	EN 717-1	E1
TVOC 28 Days	< 1000 µg/m ³	< 20 µg/m ³



FLOOR *expert*