


LURF® CLASSIC LAVI GENERAL SPECIFICATIONS

Collection	WOOD	CONCRETE
Width	180 mm	470 mm
Length	1220 mm	900 mm
Total Thickness	5 mm	5 mm
Number of Panels per Pack	10 Panels	5 Panels
M² per Pack	2,196 m²	2,144 m²
Weight per Pack	24,2 kg	21,65 kg
Wear Layer	0.5 mm	0.5 mm
Tongue and Groove	Uniclic	Uniclic
Usage Class	Class 32	Class 32

FACTORY WARRANTY			
CE	EN 14041: 2004 / AC: 2006		
Warranty	Residential Use	10-Year	10-Year
	Commercial Use	2-Year	2-Year
	Uniclic (Residential Use)	10-Year	10-Year

TECHNICAL SPECIFICATIONS		
	STANDARD	LAVI VALUES
Wear Resistance	EN 660-1/2	Group T
Impact Resistance	NALFA LF 01-2011 Section 3.6	No Cracking or Fracture
Dimensional Variance	ISO 24337	Pass
Flexibility	EN 435 Method A	Pass
Castor Chairs Suitability	EN 425	> 25000 Cycles
Chemical Resistance	EN 423	Pass
Residual Indentation	ISO 24343-1: 2007	0.02 mm
Sound Reduction	EN ISO 717-2	2 dB
Curling	EN ISO 23999	-0.15 mm
Locking Strength	ISO 24334	Pass
Electrical Resistance	EN 1815: 2016 Method A	Voltage: 0.2 kV
Dimensional Stability	EN ISO 23999	X Direction: 0.06%
		Y Direction: -0.05%
Reaction to Fire	EN 14041 / ASTM 648	Bfl-S1, Class 1
Colour Fastness to Artificial Light	ISO 105 B02: 2014	>= Grade 6
Slip Resistance	EN 13893	Class DS
Sound Testing	ASTM E90	STC: 68
	ASTM E492	IIC: 66
	ASTM E2179	Delta: 22
Thermal Resistance	EN 12664	0.12 K/W

ENVIRONMENT & CERTIFICATES		
VOC Emission		A+ (French VOC Regulation)
Indoor Air Comfort		Gold
GreenGuard		Gold
Formaldehyde Emission	EN 717-1	E1
TVOC 28 Days	< 1000 µg/m³	< 20 µg/m³



LURF® CLASSIC LAVI GENERAL SPECIFICATIONS

COLLECTION		LAVI HERRINGBONE
Width		126mm
Length		630mm
Number of panels per pack		22 Panels
m² per pack		1,746 m²
Weight per pack		18.5 kg
Total Thickness		5,0mm
Wear Layer		0,5mm
Tongue and groove		Valinge 5Gi Click
Usage Class	EN 16511	Class 32 (Heavy Commercial Use)
	EN ISO 10874	Class 42 (General light industrial use)
CE	EN 14041: 2004/ AC: 2006	
Warranty	Residential Use	10 Years
	Commercial Use	2 Years
CERTIFICATION		
Floorscore		
VOC Emission		A+ (French VOC regulation)
Indoor Air Comfort Gold		
GreenGuard Gold		
TECHNICAL DATA		
	STANDARD	LAVI
Wear resistance	EN660-1/2	Group T
Resistant to Impact	NALFA LF 01-2011 Section 3.6	No Cracking or fracture
Dimensional Variance	ISO 24337	Pass
Flexibility	EN 435 Method A	Pass
Castor chairs Suitability	EN 425	> 25000 cycles
Chemical Resistance	EN 423	Pass
Residual indentation	ISO 24343-1: 2007	0.02mm
Sound Reduction	ENISO717-2	2dB
Curling	EN ISO 23999	-0.15mm
Locking Strength	ISO 24334	Pass
Electrical Resistance	EN 1815: 2016 Method A	Voltage: 0.2kV
Dimensional Stability	EN ISO 23999	X Direction: 0.06%
		Y Direction: -0.05%
Reaction to Fire	EN 14041/ ASTM648	BF1-S1, Class 1
Color Fastness to Artificial Light	ISO 105 B02: 2014	>= Grade 6
Slip resistance	EN 13893	Class DS
Sound Testing	ASTM E90	STC: 68
	ASTM E492	IIC: 66
	ASTM E2179	Delta: 22
Thermal resistance	EN 12664	0.12K/W
DANGEROUS SUBSTANCES		
Formaldehyde emission	EN 717- 1§	E1